

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 4/1/2023

Revision: 4/1/2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: Power XD**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Degreaser
- **Uses advised against** Contact manufacturer.
- **1.3 Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**
Atlas Chemical
5209 W. Rio Vista Ave,
Tampa, FL 33634
- **1.4 Emergency telephone number:**
ChemTel Inc.
+1 (800)255-3924, +1 (813)248-0585



SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
Classifications listed are applicable to the OSHA GHS Hazard Communication Standard (29CFR1910.1200).



corrosion

- Met. Corr.1 H290 May be corrosive to metals.
- Skin Corr. 1C H314 Causes severe skin burns and eye damage.
- Eye Dam. 1 H318 Causes serious eye damage.
- **Additional information:**
There are no other hazards not otherwise classified that have been identified.
0 % of the mixture consists of component(s) of unknown toxicity.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is additionally classified and labelled according to the Globally Harmonized System within the United States (GHS).
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS05

- **Signal word** Danger

(Cont'd. on page 2)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 4/1/2023

Revision: 4/1/2023

Trade name: Power XD

(Cont'd. from page 1)

- **Hazard-determining components of labelling:**

disodium metasilicate

Poly(oxy-1,2-ethanediyl), alpha-(4-nonylphenyl)-omega-hydroxy, branched

- **Hazard statements**

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

- **Precautionary statements**

P260 Do not breathe mist/vapours/spray.

P264 Wash thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection.

P234 Keep only in original container.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P363 Wash contaminated clothing before reuse.

P310 Immediately call a POISON CENTER/doctor.

P301+P330+P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P405 Store locked up.

P406 Store in corrosive resistant container with a resistant inner liner.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **NFPA ratings (scale 0 - 4)**



Health = 3

Fire = 0

Reactivity = 0

- **HMIS-ratings (scale 0 - 4)**



Health = 3

Fire = 0

Reactivity = 0

- **2.3 Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**

- **Description:** Mixture of substances listed below with nonhazardous additions.

(Cont'd. on page 3)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 4/1/2023

Revision: 4/1/2023

Trade name: Power XD

(Cont'd. from page 2)

· Dangerous components:

CAS: 111-76-2 EINECS: 203-905-0 Index number: 603-014-00-0	2-butoxyethanol ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319	2,5-10%
CAS: 6834-92-0 EINECS: 229-912-9 Index number: 014-010-00-8	disodium metasilicate ⚠ Met. Corr.1, H290; Skin Corr. 1B, H314; Eye Dam. 1, H318 ⚠ STOT SE 3, H335	2,5-10%
CAS: 13235-36-4	EDTA, Tetrasodium Salt ⚠ Eye Dam. 1, H318 ⚠ Acute Tox. 4, H302	2,5-10%
CAS: 127087-87-0 NLP: 500-315-8	Poly(oxy-1,2-ethanediyl),alpha-(4-nonylphenyl)-omega-hydroxy, branched ⚠ Eye Dam. 1, H318 ⚠ Aquatic Chronic 2, H411 ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315	≤ 2,5%
CAS: 1310-73-2 EINECS: 215-185-5 Index number: 011-002-00-6	sodium hydroxide ⚠ Met. Corr.1, H290; Skin Corr. 1A, H314; Eye Dam. 1, H318	≤ 2,5%
CAS: 61789-40-0 EINECS: 263-058-8	Cocoamidopropyl Betaine ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319	≤ 2,5%

· SVHC

127087-87-0 | Poly(oxy-1,2-ethanediyl),alpha-(4-nonylphenyl)-omega-hydroxy, branched

· Additional information:

For the listed ingredient(s), the identity and exact percentages are being withheld as a trade secret.

SECTION 4: First aid measures**· 4.1 Description of first aid measures****· General information:**

Immediately remove any clothing soiled by the product.

Take affected persons out into the fresh air.

· After inhalation: Supply fresh air; consult doctor in case of complaints.**· After skin contact:**

Immediately rinse with water.

If skin irritation continues, consult a doctor.

Seek immediate medical help for blistering or open wounds.

· After eye contact:

Protect unharmed eye.

Remove contact lenses if worn, if possible.

Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

· 4.2 Most important symptoms and effects, both acute and delayed

Breathing difficulty

(Cont'd. on page 4)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 4/1/2023

Revision: 4/1/2023

Trade name: Power XD

(Cont'd. from page 3)

Coughing
Thirst
Caustic effect on skin and mucous membranes.
Danger of severe eye injury.
Nausea in case of ingestion.
Gastric or intestinal disorders when ingested.
Vomiting.
Diarrhea.

· **Hazards**

Danger of impaired breathing.
Danger of gastric perforation.
Causes severe skin burns and eye damage.
May be harmful if inhaled.

· **4.3 Indication of any immediate medical attention and special treatment needed**

Medical supervision for at least 48 hours.

SECTION 5: Firefighting measures

· **5.1 Extinguishing media**

· **Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.

· **For safety reasons unsuitable extinguishing agents:** None.

· **5.2 Special hazards arising from the substance or mixture**

Formation of toxic gases is possible during heating or in case of fire.

· **5.3 Advice for firefighters**

· **Protective equipment:**

Wear self-contained respiratory protective device.

Wear fully protective suit.

· **Additional information** No further relevant information available.

SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation

Particular danger of slipping on leaked/spilled product.

· **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

· **6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Send for recovery or disposal in suitable receptacles.

· **6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

(Cont'd. on page 5)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 4/1/2023

Revision: 4/1/2023

Trade name: Power XD

(Cont'd. from page 4)

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Prevent formation of aerosols.
Use only in well ventilated areas.
Use personal protective equipment as required.
- **Information about fire - and explosion protection:** No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Store only in the original receptacle.
Unsuitable material for receptacle: aluminium.
Provide ventilation for receptacles.
- **Information about storage in one common storage facility:**
Store away from foodstuffs.
Store away from oxidising agents.
Do not store together with acids.
- **Further information about storage conditions:** Keep container tightly sealed.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see section 7.
- **8.1 Control parameters**

Ingredients with limit values that require monitoring at the workplace:

111-76-2 2-butoxyethanol

IOELV (EU)	Short-term value: 246 mg/m ³ , 50 ppm Long-term value: 98 mg/m ³ , 20 ppm Skin
PEL (USA)	Long-term value: 240 mg/m ³ , 50 ppm Skin
REL (USA)	Long-term value: 24 mg/m ³ , 5 ppm Skin
TLV (USA)	Long-term value: 97 mg/m ³ , 20 ppm BEI
EL (Canada)	Long-term value: 20 ppm
EV (Canada)	Long-term value: 20 ppm Skin

1310-73-2 sodium hydroxide

PEL (USA)	Long-term value: 2 mg/m ³
REL (USA)	Ceiling limit: 2 mg/m ³

(Cont'd. on page 6)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 4/1/2023

Revision: 4/1/2023

Trade name: Power XD

(Cont'd. from page 5)

TLV (USA)	Ceiling limit: 2 mg/m ³
EL (Canada)	Ceiling limit: 2 mg/m ³
EV (Canada)	Ceiling limit: 2 mg/m ³

- **DNELs** No further relevant information available.
- **PNECs** No further relevant information available.

· **Ingredients with biological limit values:**

111-76-2 2-butoxyethanol

BEI (USA)	200 mg/g creatinine Medium: urine Time: end of shift Parameter: Butoxyacetic acid with hydrolysis
-----------	--

- **8.2 Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
The usual precautionary measures are to be adhered to when handling chemicals.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
- **Respiratory protection:**
Not required under normal conditions of use.
Use suitable respiratory protective device when high concentrations are present.
Use suitable respiratory protective device when aerosol or mist is formed.
For large spills, respiratory protection may be advisable.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Eye protection:**
Contact lenses should not be worn.



Safety glasses

- **Body protection:** Protective work clothing
- **Limitation and supervision of exposure into the environment** Avoid release to the environment.

(Cont'd. on page 7)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 4/1/2023

Revision: 4/1/2023

Trade name: Power XD

· Risk management measures See Section 7 for additional information.

(Cont'd. from page 6)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form:	Liquid
Colour:	Purple
Odour:	Mild
Odour threshold:	Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range:	Not determined.
Boiling point/Boiling range:	Not determined.

· Flash point: Not applicable.

· Flammability (solid, gaseous): Not applicable.

· Auto/Self-ignition temperature: Not determined.

· Decomposition temperature: Not determined.

· Self-igniting: Product is not self-igniting.

· Danger of explosion: Product does not present an explosion hazard.

· Explosion limits:

Lower:	Not determined.
Upper:	Not determined.

· Oxidising properties: Not determined.

· Vapour pressure: Not determined.

· Density: Not determined.

· Relative density: Not determined.

· Vapour density: Not determined.

· Evaporation rate: Not determined.

· Solubility in / Miscibility with water:

Fully miscible.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not determined.

Kinematic: Not determined.

· 9.2 Other information: No further relevant information available.

(Cont'd. on page 8)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 4/1/2023

Revision: 4/1/2023

Trade name: Power XD

(Cont'd. from page 7)

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability** Stable under normal temperatures and pressures.
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **10.3 Possibility of hazardous reactions**
Reacts with strong oxidising agents.
Strong exothermic reaction with acids.
Reacts with various metals.
Reacts with fats and oils.
Attacks materials containing glass and silicate.
- **10.4 Conditions to avoid**
Avoid acids.
Store away from oxidising agents.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**
Carbon monoxide and carbon dioxide
Nitrogen oxides (NOx)
Ammonia

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

111-76-2 2-butoxyethanol

Oral	LD50	1480 mg/kg (rat)
Dermal	LD50	400 mg/kg (rab)
Inhalative	LC50/4h	450 ppm (rat)

127087-87-0 Poly(oxy-1,2-ethanediyl),alpha-(4-nonylphenyl)-omega-hydroxy, branched

Oral	LD50	1410 mg/kg (rat)
Dermal	LD50	2830 mg/kg (rabbit)

1310-73-2 sodium hydroxide

Oral	LD50	2000 mg/kg (rat)
------	------	------------------

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes severe skin burns and eye damage.
- **Serious eye damage/irritation**
Causes serious eye damage.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Acute effects (acute toxicity, irritation and corrosivity):**
Causes severe skin burns and eye damage.
May be harmful if inhaled.

(Cont'd. on page 9)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 4/1/2023

Revision: 4/1/2023

Trade name: Power XD

(Cont'd. from page 8)

- **Repeated dose toxicity:** No further relevant information available.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction):**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

127087-87-0 Poly(oxy-1,2-ethanediyl),alpha-(4-nonylphenyl)-omega-hydroxy, branched

LC50 > 3,8 mg/l (pimephales promelas)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.

· Additional ecological information:

· General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Rinse off of bigger amounts into drains or the aquatic environment may lead to increased pH-values. A high pH-value harms aquatic organisms. If the dilution of the use-level pH-value is considerably reduced, the aqueous waste, emptied into drains, is only low water-dangerous.

· 12.5 Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Can be disposed of with household garbage with prior chemical-physical or biological treatment following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.

(Cont'd. on page 10)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 4/1/2023

Revision: 4/1/2023

Trade name: Power XD

(Cont'd. from page 9)

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN-Number	UN3266
· DOT, ADR, IMDG, IATA	
· 14.2 UN proper shipping name	Corrosive liquid, basic, inorganic, n.o.s. (Sodium hydroxide)
· DOT, IATA	
· ADR	3266 CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (SODIUM HYDROXIDE)
· IMDG	CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (SODIUM HYDROXIDE)
· 14.3 Transport hazard class(es)	
· DOT	
	
· Class	8 Corrosive substances.
· Label	8
· ADR	
	
· Class	8 (C5) Corrosive substances.
· Label	8
· IMDG, IATA	
	
· Class	8 Corrosive substances.
· Label	8
· 14.4 Packing group	
· DOT, ADR, IMDG, IATA	III
· 14.5 Environmental hazards:	Not applicable.
· 14.6 Special precautions for user	Warning: Corrosive substances.
· Danger code (Kemler):	80
· EMS Number:	F-A,S-B

(Cont'd. on page 11)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 4/1/2023

Revision: 4/1/2023

Trade name: Power XD

(Cont'd. from page 10)

· Segregation groups	Alkalis
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
· Tunnel restriction code	E
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 3266 CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (SODIUM HYDROXIDE), 8, III

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- United States (USA)
- SARA

· Section 355 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

111-76-2 | 2-butoxyethanol

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Proposition 65 (California):

· Chemicals known to cause cancer:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

(Cont'd. on page 12)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 4/1/2023

Revision: 4/1/2023

Trade name: Power XD

(Cont'd. from page 11)

- **Carcinogenic Categories**

- **EPA (Environmental Protection Agency)**

111-76-2 | 2-butoxyethanol

NL

- **IARC (International Agency for Research on Cancer)**

111-76-2 | 2-butoxyethanol

3

- **TLV (Threshold Limit Value established by ACGIH)**

111-76-2 | 2-butoxyethanol

A3

- **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients are listed.

- **Canada**

- **Canadian Domestic Substances List (DSL)**

All ingredients are listed.

- **Canadian Ingredient Disclosure list (limit 0.1%)**

None of the ingredients are listed.

- **Canadian Ingredient Disclosure list (limit 1%)**

111-76-2 | 2-butoxyethanol

6834-92-0 | disodium metasilicate

1310-73-2 | sodium hydroxide

- **Directive 2012/18/EU**

- **Named dangerous substances - ANNEX I**

None of the ingredients are listed.

- **Other regulations, limitations and prohibitive regulations**

- **Substances of very high concern (SVHC) according to REACH, Article 57**

127087-87-0 | Poly(oxy-1,2-ethanediyl),alpha-(4-nonylphenyl)-omega-hydroxy, branched

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

H290 May be corrosive to metals.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

(Cont'd. on page 13)

Safety Data Sheet
according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 4/1/2023

Revision: 4/1/2023

Trade name: Power XD

(Cont'd. from page 12)

H411 Toxic to aquatic life with long lasting effects.

Abbreviations and acronyms:

Met. Corr.1: Corrosive to metals, Hazard Category 1
Acute Tox. 4: Acute toxicity, Hazard Category 4
Skin Corr. 1A: Skin corrosion/irritation, Hazard Category 1A
Skin Corr. 1B: Skin corrosion/irritation, Hazard Category 1B
Skin Corr. 1C: Skin corrosion/irritation, Hazard Category 1C
Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1
Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2
STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3
Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

Sources

Website, European Chemicals Agency (<http://http://echa.europa.eu/>)
Website, US EPA Substance Registry Services (http://http://ofmpub.epa.gov/sor_internet/registry/substreg/home/overview/home.do)
Website, Chemical Abstracts Registry, American Chemical Society (<https://www.cas.org>)
Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: ISBN: 978-0-470-07488-6
Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5.
Safety Data Sheets, Individual Manufacturers
SDS Prepared by:
ChemTel Inc.
1305 North Florida Avenue
Tampa, Florida USA 33602-2902
Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573
Website: www.chemtelinc.com